



division of Fiberglass Systems, Inc.
 4545 Enterprise Street Boise, ID 83705
 ph.: 800-727-9907 fax: 800-627-0929 www.best-bath.com

Specification

Grab Bar Stainless Steel Straight

Tubing material: Type 304 (18-8) stainless steel

Tubing size: 1-1/4" O.D. x .049" (18 ga.) wall thickness

Tubing size: 1-1/2" O.D. x .049" (18 ga.) wall thickness

Flange style:

Mounting flanges are constructed of Type 304 (18-8) stainless steel, heliarc welded to the bar to form a single structural unit. Concealed, 14 ga. x 3" dia.

Finish:

Standard - satin stainless
 Optional Powder coating (P.C.) in various colors
 Epoxy type DuPont #ELW-505-S9
 Adhesion per ASTM D3359 Method B
 Accelerated aging per ASTM G26 Method A
 Gloss per ASTM D 523
 Flexibility per ASTM D 522 Method A

Meets:

- ADA Guidelines section 4.26
- ASTM F 466-85 (re-approved 1990): Standard Consumer Safety Specification for Grab Bars and Accessories installed in the Bathing Area
- Federal Specification WW-P 541-8b, amendment 1 4-16-1990
- ANSI 117.1 1998: Buildings and Facilities providing Accessibility and Usability
- F.H.A., V.A. and HUD requirements
- Commonwealth of Massachusetts Architectural Access Board
- California Building Code
- City of Los Angeles

Installation:

Factory Installed with #10x1-1/4" stainless TEK screws in integral plywood backing.

